

YCB TYPE GEAR OIL PUMP



Main Specification

YCB Series Gear Oil Pump used to delivery non-corrosive lubricating oil or similar liquid without Particle and fibers.

Temperature is not higher than 80 °C, the viscosity is 5×10^{-6} - 1.5×10^{-3} m² / s (5 to 1500 CST) nature of lubricating oil or other liquids, such as lubricating oil, and used in hydraulic transmission systems.

Type	Capacity	Speed	Pressure	NPSH	Efficiency	Motor	
	m3/h	r/min	Mpa	m	%	Hz	kw
YCB0.6-0.6	0.6	910	0.6	5.5	60	50	0.75
	1	1390				50	0.75
	0.7	1130				60	0.75
	1.2	1710				60	0.75
YCB0.6-1.6	0.6	910	1.6	7	70	50	1.1
	1	1400				50	1.5
	0.7	1130				60	1.1
	1.2	1710				60	1.5
YCB1.6-0.6	1.6	910	0.6	5.5	63	50	0.75
	2.5	1400				50	1.1
	1.9	1130				60	1.1
	3	1710				60	1.1
YCB1.6-1.6	1.6	940	1.6	7	71	50	2.2
	2.5	1400				50	4
	1.9	1150				60	2.2
	3	1750				60	4
YCB3.3-0.6 (More size, please contact us)	3.3	940	0.6	5	60	50	1.5
	5	1420				50	2.2
	4	1150				60	1.5
	6	1730				60	2.2