

MARINE HALF TWIST-ACTION HAND PUMP



Main Specification

Centrifugal pump is a high quality Marine cargo pump, used for transporting gasoline, kerosene, diesel, aviation kerosene oil products, such as medium temperature in the -20℃- 80℃, also can be transported with seawater, freshwater etc.

Type	Capacity		Head	NPSH	Ability of Self-Priming	Speed	Axle-power	Sunction/Dis-charge port
	m3/h	L/min	m	m	min/5m	r/min	kw	mm
25CZY-27	3	50	27	3	3	2900	0.6	25
40CZY-20	6.3	105	20	3.5	2	2900	0.88	40×32
40CZY-40	10	167	40	3.5	1.5	2900	2.8	50×40
50CZY-12	15	250	12	3.5	2.5	2900	1.1	50
50CZY-20	18	300	20	3.5	2	2900	1.8	50
50CZY-35	14	233	35	3.5	1.5	2900	2.7	50
50CZY-50	12.5	208	50	3.5	1.5	2900	4.3	50
50CZY-60	15	250	60	3.5	1.5	2900	6.3	50
50CZY-75	20	333	75	3.5	1.5	2900	9.9	50
65CZY-15	30	500	15	4	2	2900	1.92	65
65CZY-30	25	416	30	4	2	2900	3.2	65
80CZY-13	35	583	13	4	3.5	2900	1.9	80
80CZY-17	43	716	17	4	2	2900	3.1	80
80CZY-25	50	833	25	4	1.5	2900	5.2	80
80CZY-32	50	833	32	4	1.5	2900	6.8	80