

RY SERIES AIR COOLED HOT OIL PUMP



Main Specification

Type RY air-cooled hot oil pump is the energy conservation production designed and manufactured on the standard GB5662.

With scientific construction and fine capacity, it is used in transporting high temperature liquid without solid particles. And the degree of corrosion resisting and working temperature is depended on the material of the main parts which connected with the medium.

Type	Capacity	Head	Speed	Power(kw)		Efficiency	Motor
	m3/h			m	r/min		
15-15-100	3	10	2800	0.45	0.75	20	801
15-15-100A	2	10	2800	0.36	0.55	18	AO2-7122
15-15-100B	1	10	2800	0.2	0.37	15	AO2-7112
20-20-100	1	10	2800	0.09	0.37	26	AO2-7112
20-20-125	1.5	22	2800	0.22	0.75	30	801
40-25-160	10	28	2900	1.72	2.2	45	90L
25-25-160	3	27	2900	0.53	1.5	30	90S
32-32-160	6	28	2900	0.85	1.5	50	90S
50-32-160	12.5	30	2900	1.9	3	57	100L
50-32-200	18	40	2900	3.92	5.5	50	132SI
50-32-200A	16	32	2900	3.35	4	42	112M
50-32-250	12.5	80	2900	6.2	11	44	160MI
65-50-160	20	32	2900	3.17	5.5	55	132S1
65-40-200	30	48	2900	6.3	7.5	62	132S2
65-40-200A	25	35	2900	4	5.5	59	132S1
65-40-250	25	80	2900	10.3	15	53	160M2