

# FS SERIES MARINE UPDRAFT SUBERSIBLE PUMP



## Main Specification

FS series is suitable for conveying temperature not exceed 40 °C, sediment concentration or insoluble in water volume ratio less than 0.1% of solid particles, particle size is not more than 0.2 mm of water or weak corrosive liquid and water supply and drainage, etc.

| Type          | Capacity<br>m <sup>3</sup> /h | Head<br>m | Power<br>kw | Current<br>A | Caliber<br>mm | Weight<br>kg |
|---------------|-------------------------------|-----------|-------------|--------------|---------------|--------------|
| FS8.4-40-2.2  | 8.4                           | 40        | 2.2         | 5.7          | 40            | 45           |
| FS15-26-2.2   | 15                            | 26        | 2.2         | 5.7          | 40            | 49           |
| FS25-17-2.2   | 25                            | 17        | 2.2         | 5.7          | 50            | 41           |
| FS65-7-2.2    | 65                            | 7         | 2.2         | 5.7          | 100           | 41           |
| FS100-4.5-2.2 | 100                           | 4.5       | 2.2         | 5.7          | 128           | 38           |
| FS8.4-50-3    | 8.4                           | 50        | 3           | 7.54         | 40            | 47           |
| FS12.5-40-3   | 12.5                          | 40        | 3           | 7.54         | 40            | 47           |
| FS15-36-3     | 15                            | 36        | 3           | 7.54         | 40            | 46           |
| FS20-30-3     | 20                            | 30        | 3           | 7.54         | 40            | 48           |
| FS25-36-3     | 25                            | 26        | 3           | 7.54         | 50            | 46           |
| FS40-16-3     | 40                            | 16        | 3           | 7.54         | 65            | 47           |
| FS65-10-3     | 65                            | 10        | 3           | 7.54         | 100           | 45           |
| FS100-6-3     | 100                           | 6         | 3           | 7.54         | 128           | 48           |
| FS160-4-3     | 160                           | 4         | 3           | 7.54         | 128           | 43           |
| FS12.5-50-4   | 12.5                          | 50        | 4           | 8.9          | 40            | 59           |
| FS25-32-4     | 25                            | 32        | 4           | 8.9          | 50            | 57           |
| FS40-21-4     | 40                            | 21        | 4           | 8.9          | 65            | 54           |
| FS65-13-4     | 65                            | 13        | 4           | 8.9          | 100           | 51           |
| FS200-4-4     | 200                           | 4         | 4           | 8.9          | 150           | 52           |
| FS20-50-5.5   | 20                            | 50        | 5.5         | 12           | 50            | 75           |
| FS25-40-5.5   | 25                            | 40        | 5.5         | 12           | 50            | 76           |
| FS40-28-5.5   | 40                            | 28        | 5.5         | 12           | 65            | 83           |
| FS100-12-5.5  | 100                           | 12        | 5.5         | 12           | 125           | 65           |