

FX SEIRES MARINE DOWNDRAFT SUMERSIBLE PUMP



Main Specification

FX Seires Marine downdraft Sumersible Pump are used to transport the freshwater and other purpose the temperature is not higher than 40℃, solid granules is not more than 0.2mm. Impeller with against pine device, Mechanical seal face material USES silicon carbide - silicon carbide, durable, safe and reliable.

Type	Capacity		Head (m)	Power (kW)	Current (A)	Caliber (mm)	Weight (kg)
	(m3/h)	(l/s)					
FX10-14-0.75	10	2.8	14	0.75	1.8	40	40
FX6-25-1.1	6	1.7	25	1.1	2.73	25	25
FX10-18-1.1	10	2.8	18	1.1	2.73	40	25
FX15-14-1.1	15	4.2	14	1.1	2.73	40	25
FX25-9-1.1	25	6.9	9	1.1	2.73	50	25
FX40-6-1.1	40	11.1	6	1.1	2.73	65	34
FX10-24-1.5	10	2.8	24	1.5	3.87	40	32
FX10-34-2.2	10	2.8	34	2.2	6	40	39
FX25-30-3	25	6.9	30	3	6.5	50	45
FX15-45-4	15	4.2	45	4	8.6	40	49
FX25-32-4	25	6.9	32	4	8.6	50	49
FX25-40-5.5	25	6.9	40	5.5	12	50	64